



SURGEX™

BOILER TREATMENT

DESCRIPTION

SURGEX™ helps to eliminate priming, surging, and foaming by reacting with foaming bubbles by breaking them up. SURGEX™ contains inhibitors that prevent corrosion and hard water mineral scale.

CHARACTERISTICS

- * Cures and prevents surging and priming
- * Produces clean, dry steam and steady water gauge.
- * Will not harm synthetic seals or gaskets
- * Inhibits corrosion and scale.
- * Contains no petroleum distillates
- * Color coded for accurate dosage

APPLICATIONS

SURGEX™ is used to cure priming, surging and foaming in boilers. SURGEX™ is especially effective in inhibiting scale and corrosion.

PACKAGING

<u>Code</u>	<u>Size</u>	<u>Qty./Case</u>	<u>Lbs./Case</u>	<u>Cu. Ft./Case</u>
68752	1.5 Oz.	20	7	0.17

SURGEX™ BOILER TREATMENT

INSTRUCTIONS

READ ALL DIRECTIONS, MSDS AND WARNINGS ON LABEL BEFORE USING

- If possible, drain boiler if other boiler compounds have been used. Refill boiler .
- Relieve pressure. Add 1 SURGEX™ per 600 sq. ft. radiation, through safety valve.
- Fire boiler for 15 minutes. If water in gauge glass is not green, add more SURGEX™.

For additional technical information, call Toll Free 1-800-231-3345

PRECAUTIONS

**FOR CHEMICAL EMERGENCY, SPILL, LEAK, FIRE, EXPOSURE OR ACCIDENT,
CALL CHEMTREC - DAY OR NIGHT 1-800-424-9300**

WARNING: EYE IRRITANT. KEEP OUT OF REACH OF CHILDREN.

FIRST AID: Eyes: Flush eyes with water for 15 minutes. Skin: Wash with soap and water.

For additional information, refer to Material Safety Data Sheet.

SPECIFICATIONS

Wt/Gal @ 77°F	Solid
Flash Point SETA CC	None
Color	Orange powder
Shelf Life	2 years minimum

Suggestions and recommendations covering the use of our products are based on our past experience and laboratory findings. However, as we have no control as to the methods and conditions of application, we only assume responsibility for the uniformity of our products within manufacturing tolerances.

LIMITED WARRANTY

Rectorseal® makes the Limited Express Warranty that when the instructions for storage and handling of our products are followed we warrant our products to be free from defects. **THIS LIMITED EXPRESS WARRANTY IS EXPRESSLY IN LIEU OF ANY OTHER EXPRESS OR IMPLIED WARRANTIES, INCLUDING ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, AND OF ANY OTHER OBLIGATION ON THE PART OF RECTORSEAL®.** The sole remedy for breach of the Limited Express Warranty shall be the refund of the purchase price. All other liability is negated and disclaimed, and Rectorseal® shall not be liable for incidental or consequential damages.

MANUFACTURED IN U.S.A. BY
Rectorseal® • 2601 Spenwick Drive • Houston, Texas 77055-1035
Telephone: 713-263-8001 or 1-800-231-3345 Fax: 713-263-7577 or 1-800-441-0051
www.rectorseal.com

A-02